



xBeacon1

Ideal for both engagement and presence applications. The xBeacon1 is a single transmitter beacon that can engage Bluetooth LE devices in proximity. The xBeacon1 transmits a wireless BLE signal that can be used to trigger events and engage mobile clients regardless of smartphone operating system. The xBeacon1 also supports a variety of business optimization applications such as workforce management, asset management, tracking and logistics.

Product Highlights

- + Ease of Maintenance
- + Multiple mounting options available
- + Configurable transmit power and receive sensitivity
- + Flexible form factors and power options
- + Seamless integration with PayX gateways
- + White-label housings
- + On-premise or Cloud Data Analytics
- + Extended battery-life (battery powered models)
- + Plug-n-Play Deployment
- + Integrated enterprise security (AES, SHA, ECC)
- + Cloud connectivity (Wi-Fi, Ethernet, Mesh)
- + Sleek industrial design
- + Supports multiple enterprise applications

Industries

Hospitality

- + Guest Dwell Time & Analytics
- + Effortless Check-in
- + New & Return Visitors Analytics
- + Footpath & Way Finding
- + Branded, Private Wi-Fi
- + Customized Messaging & On-property Offerings

Retail

- + In-Store Analytics
- + Footpath & Way Finding
- + Private Wi-Fi
- + Proximity Marketing & Discount Offers
- + Sales Conversion
- + Mobile Payments

Brands

- + Branded, Private Wi-Fi
- + Proximity Marketing

Marketing Agencies

- + Capitalize on New Technologies to Win Business
- + Contextual Offers
- + Granular Insight to Individuals & their Shopping Habits
- + Possess the Ability to Market to the Customer while in the Store

Healthcare

- + High Value Asset Tracking
- + Footpath & Way Finding

Out-Of-Home

- + Trigger Personalized Messages on Digital Signature

Logistics

- + Track Valuable Assets Anywhere in the World
- + Measure Temperature, Humidity, Lighting, Barometer Speed, Elevation

Technical Specifications

DIMENSIONS	USB 18 x 13 x 5 mm (0.7 x 0.51 x 0.2 in) Lithium Battery (Coin Cell 2477) 38 x 28 x 10 mm (1.5 x 1.1 x 0.4 in) High Capacity Lithium Battery (19,000mAh)
-------------------	---

WEIGHT	0.1 oz. / 2.8 g (USB) 0.6 oz. / 18 g (with Lithium Battery)
---------------	--

PROCESSOR	ARM Cortex M0 MCU
------------------	-------------------

OPERATING SYSTEM	n/a
-------------------------	-----

REMOVABLE STORAGE	n/a
--------------------------	-----

WI-FI FEATURES	n/a
-----------------------	-----

BLUETOOTH LE FEATURES	Apple's iBeacon Google's Eddystone L2CAP, ATT, GATT, GAP Peripheral & Central Mode
------------------------------	---

BLUETOOTH CLASSIC FEATURES	n/a
-----------------------------------	-----

ENVIRONMENT	Operating Temperature: -40°C to 85°C Humidity: 5 to 95% Non-Condensing
--------------------	--

RADIO FREQUENCIES	Wi-Fi: n/a Bluetooth LE: 2.4GHz
--------------------------	------------------------------------

OUTPUT POWER	Wi-Fi: n/a Bluetooth LE: Up to 0dBm (Rx -93dBm)
---------------------	--

RANGE	Wi-Fi (LOS): n/a Bluetooth LE (LOS): 30-100m
--------------	---

POWER SUPPLY	Battery: AA or Lithium Coin Cell USB input: 5 V DC @ 500mA max Indoor Ambient Light: Amorphous Silicon (a-Si) PV cell
---------------------	---

OPTIONAL MOUNTING OPTIONS	Adjustable Mounting Bracket Ceiling / Wall Mounting Plate Weatherproof Package Charging Clip
----------------------------------	---

APPLICATIONS	Proximity Beacon Asset Tagging (Active RFID) Workforce Management Supply Chain Logistics IoT sensing applications
---------------------	---



Depth
28mm (1.1 in)

Width
38mm (1.5 in)



Height
10mm (.4 in)